

GUAGE BRASS VALVE WITH TEST PORT PN 16

Material
Pressure

brass / forged
PN 16

APPLICATIONS

Forged brass guage valve. It is used as a shut-off valve installed before a pressure gauge, its purpose is to ensure repair or replacement of the pressure gauge without having to stop the system.

- the valve is equipped with a control flange Ø40x5mm.
- suitable for pressure gauges with seal according to DIN EN 837-1
- construction according to DIN 16261-B

VARIANTS

Thread connection: Male/Female

Connection size: Thread: BSPP G 1/4", G 3/8", G 1/2"



No.	DETAILS	MATERIALS
1	Body	forged brass
2	Spindle	brass
3	Lever	plastic

SPECIFICATION	
Standard	DIN
P max. operating pressure	16 Bar
T max operating temperature	90 [°C]
Operation	Manual
Weight	0.15 kg
Inlet	1/4" (BSPP)
	3/8" (BSPP)
	1/2" (BSPP)
Outlet	1/4" (BSPP)
	3/8" (BSPP)
	1/2" (BSPP)
Test connection (mm)	Ø40

GUAGE BRASS VALVE WITH TEST PORT PN 16

Material brass / forged
Pressure PN 16

DN	accession	working pressure (Bars)	(kg)
4	G 1/4"	0 - 16.0 Bar	0.15
4	G 3/8"	0 - 16.0 Bar	0.15
4	G 1/2"	0 - 16.0 Bar	0.15