

GUAGE BRASS VALVE THREE-WAY PN 250

Material
Pressure

brass / forged
PN 250

APPLICATIONS

Three-way gauge needle valve. It is used as a shut-off valve installed before a manometer, its purpose is to ensure repair or replacement of the manometer without having to stop the system. A threaded hole is made in the lower part of the valve, which can be used as a test connection if necessary.

VARIANTS

Thread connection: Male/Female

Connection thread: M20x1.5; G 1/2"



			SPECIFICATION	
No.	DETAILS	MATERIALS	Standard	DIN
1	Body	brass	P max. working pressure	250 Bar
2	Packing seal	Teflon / PTFE	T max operating temperature	120 °C
3	Spindle	stainless steel 1.4104 / AISI 316L	Management	manually with wheel
4	Drive wheel	plastic	Weight	0.855 kg
5	Clamping sleeve	steel 1.0619	Inlet	1/2" (BSPP)
				M20 x 1.5
			Outlet	1/2" (BSPP)
				M20 x 1.5

GUAGE BRASS VALVE THREE-WAY PN 250

Material brass / forged
Pressure PN 250

DN	joining	working pressure (Bars)	(kg)
4	G1/2"	0 - 250.0	0.855
4	M20 x 1.5"	0 - 250.0	0.855