

PLATE FLANGE TYPE 01/B1 EN1092-1 PN63


Material	steel EN P245GH
Pressure	PN 63

TECHNICAL DESCRIPTION

Flat flanges according to standard EN1092-1 / type 01 / B1 are pipeline elements with a wide size range, which are widely used in the construction of steel pipelines and pipe segments (spools) used in industry, industry, shipbuilding and ship repair.

We stock flat steel flanges according to EN1092-1 type 01 / with sealing surface B1, but we also have the necessary machining equipment, which allows us to offer flanges with sealing surfaces.

- sealing surface type A, B2, C, D, E, F
- non-standard sealing surfaces on request
- profile grooves for metal sealing rings (segments) type RTJ
- threaded type flanges
- flanges made to customer specifications, and others.



SUPPORTED MATERIALS IN STOCK:

- Carbon steel

P245GH (1.0352) / EN 10222-2

Dimensions: DN 10 - 400

PLATE FLANGE TYPE 01/B1 EN1092-1 PN63

Material steel EN P245GH
Pressure PN 63

No.	DETAILS	MATERIALS	STANDARD
1	FLAT FLANGE 01/B1 EN1092-1 PN63	steel P245GH / (1.0352)	EN 10222-2
	other steels - on request		
		P245GH / 1.0352	EN 10222-2
		P265GH / 1.0425	EN 10028-2
		P280GH / 1.0426	EN 10222-2
		P355NL1 / 1.0566	EN 10028-3
		16Mo3; 15Mo3 / 1.5415	EN 10222-2
	other stainless steels - on request		
		AISI 304L (X2CrNiMo17-12-2) / 1.4404	EN 10222-5
		AISI 316L (X2CrNiMo17-12-2) / 1.4404	EN 10222-5
		AISI 321 (X6CrNiTi18- 10) / 1.4541	EN 10222-5
		AISI 316Ti (X6CrNiMoTi17-12-2) / 1.4571	EN 10222-5

SPECIFICATION

Standard	EN 1092-1 01/B1
Pressure	PN 63

PLATE FLANGE TYPE 01/B1 EN1092-1 PN63

Material

steel EN P245GH

Pressure

PN 63

DN	pipe Ø	flange dimensions								fastener dimensions	
	A	B1	D	K	d1	f1	C1	L	kg	n	M
10	13.5*	14	100	70	40	2	20	14	1.02	4	M12
	17.2	18							1.00		
15	20.0*	20.5	105	75	45	2	20	14	1.11	4	M12
	21.3	22.0							1.10		
20	25.0*	26	130	90	58	2	22	18	1.87	4	M16
	26.9	27.5							1.86		
25	30.0*	32	140	100	68	2	24	18	2.39	4	M16
	33.7	34.5							2.36		
32	38.0*	39	155	110	78	2	24	22	2.84	4	M20
	42.4	43.5							2.79		
40	44.5*	45.5	170	125	88	3	26	22	3.63	4	M20
	48.3	49.5							3.57		
50	57.0*	158	180	135	102	3	26	22	4.94	4	M20
	60.3	61.5							4.90		
65	76.1	77.5	205	160	122	3	26	22	4.72	8	M20
80	88.9	90.5	215	170	138	3	30	22	5.88	8	M20
100	108.0*	109	250	200	162	3	32	26	8.34	8	M24
	114.3	116							8.03		
125	133.0*	135	295	240	188	3	34	30	12.08	8	M27
	139.7	141.5							11.71		
150	159.0*	161	345	280	218	3	36	33	17.56	8	M30
	168.3	170.5							16.86		
200	219.1	221.5	415	345	285	3	48	36	30.44	12	M33
250	273.0	276.5	470	400	345	3	55	36	42.09	12	M33
300	323.9	327.5	530	460	410	4	65	136	58.98	16	M33
350	355.6	359.5	600	525	465	4	72	39	88.64	16	M36
400	406.4	411	670	585	535	4	80	42	120.80	16	M39
diameters not specified in standard EN 1092-1:2013 - can be made to order											