

CRYOGENIC GATE VALVE TYPE 01331 WELDED

Material stainless steel 1.4308
Pressure PN 50

TECHNICAL DESCRIPTION


Cryogenic shut-off and check valves, PN50
(DN150=PN40)

· stainless steel body and bronze bonnet · pre-stressed gland · cleaned and degreased for oxygen service Butt weld ends acc. to ISO 1127 and ASTM A312: · Part No. 01331.X.000* Valves · Part No. 01331.X.500* Check valves Welding sockets acc. to ISO 1127 and ASTM A312: · Part No. 01331.X.0004 Valve · Part No. 01331.X.5004 Check valves WORKING FLUID / MEDIUM

Approved for gases, vapors and liquefied cryogenic gases and LNG.

OPTIONS

· welded sleeves for stainless steel pipes according to ISO 1127 and ASTM A312 - length FF + 200mm · regulating valve (with threaded connection) · wall thickness of extension pipes



Dimensions: DN 10 - 100

CRYOGENIC GATE VALVE TYPE 01331 WELDED

Material stainless steel 1.4308

Pressure PN 50

No.	Materials	DIN EN	ASTM
1	Body	1.4308	A351CF8
2	Saddle up to DN50	Teflon PTFE / graphite filler (25%)	
2a	DN65 saddle	Teflon PTFE	
3	Valve	brass CW614N	B283 UNS C38500
4	Lid gasket	Teflon PTFE	
5	Upper part	CC493K	B505 UNS C93200
6	Bolts	1.4301/A2	A 194 B8
8	Spindle	1.4301	A276 type 304
9	Salnikov condensed.	graphite / Teflon PTFE	
10	Packing nut	brass CW614N	B283 UNS C38500
11	Flywheel	aluminum alloy	
12	Spring	CW452K	B159 UNS C51900

SPECIFICATION

Type 01331	valve/return valve PN 50 (DN150=PN40)
Connection ends	for forehead welding
Construction length	construction normal
Attaching the lid	flanged
Execution	straight
Joining	on a weld
Drive	manually
Working temp. [°C]	-196 °C / -321 °F
	+120 °C / +248 °F
Recommended temp. [°C]	-60°C / -76°F
	+120 °C / +248 °F

CRYOGENIC GATE VALVE TYPE 01331 WELDED

Material stainless steel 1.4308

Pressure PN 50

DN	Size code (X.)	Construction length (FF)	Height (H)	Pipe Ø ISO 1127 (RA)	Wall thickness ISO 1127 (a)	OD pipe Ø ASTM A312 (RA)	Wall thickness ASTM A312 (a)	Socket depth (b)	Flywheel Ø (B)	Hex size (S1)	Hex size (S2)	Weight (kg)	Kvs (m³/h)	Cv (gal/min)
10	1012	70	140	12.0	1.0	13.72	S10 or S40	6	100	7	30	1.0	1.6	1.9
15	1517	85	140	17.2	1.6	17.15	S10 or S40	10	100	7	30	1.25	3.8	4.4
15	1521	85	140	21.3	2.0	21.34	S10 or S40	10	100	7	30	1.3	4.3	5.0
20	2026	100	140	26.9	2.0	26.67	S10 or S40	13	100	7	30	1.7	6.7	7.8
25	2533	115	140	33.7	2.0	33.40	S10 or S40	13	100	7	30	2.0	11.5	13.4
32	3238	115	170	38.0	2.0	-	S10 or S40	-	125	10	36	2.8	14.0	16.2
40	4042	130	175	42.4	2.0	42.16	S10 or S40	13	125	10	36	4.2	20.6	23.9
40	4048	130	175	48.3	2.0	48.26	S10 or S40	13	125	10	36	4.2	22.6	26.3
50	5060	155	200	60.3	2.0	60.32	S10 or S40	16	125	10	36	6.7	37.1	43.2
65	657x	205	260	76.1	2.6	73.02	S10 or S40	16	200	10	36	10.7	71.1	82.7
80	8088	245	310	88.9	3.2	88.90	S10 or S40	16	250	10	36	16.0	104.0	120.9
100	0114	280	350	114.3	6.0	114.30	S10 or S40	20	315	12	41	22.0	170.0	195.2
150	0168	400	420	168.3	7.1	168.27	S10 or S40	20	360	15	41	54.1	350.0	401.8